


Lexus UX 03/2019 >>

Part No: TO-299-07U

Electric wiring kit for towbars / 7-pin / 12N / 12 Volt / ISO 1724

**Fitting instructions** 







## **IMPORTANT!**

This electric kit has to be installed by a professional workshop or a suitable qualified person.

The installation instructions must have been read and fully understood before the start of any installation. Please contact your wiring kit provider or the hotline shown in the footer

Make sure the vehicle is approved/homologated by the manufacturer to tow a trailer!

Also please check that there is a definite compatibility between this vehicle and the electric kit!

Following the installation of the electric kit, the fitting instructions should be kept together with the vehicle service document and vehicle handbook. The fitting instructions contain important information relating to the use and function of the towing kit as well as for any diagnostic or activation process, that might have to be repeated in the future (e.g. after the performance of a vehicle software update).

All warranty claims will be forfeited if the electric kit or components contained therein are used incorrectly or modified. If a towing socket adaptor has been used to connect to the trailer or bike rack, this must be removed from the trailer socket once the trailer or bike rack has been disconnected

If the trailer or bike rack is not equipped with a rear fog lamp, depending on the towing vehicle type, the correct function of the towing kit cannot be guaranteed. In such cases, a rear

This towing electric kit will not be covered under warranty if any technical or electrical modifications or software updates have been performed by the vehicle manufacturer after the initial commissioning of the kit. That applies especially to modifications or updates which may cause malfunctions in the trailer socket or any other part of the trailer electrical equipment!

Depending on the type of trailer module used in this electric kit, diagnostic interrogation with the vehicle's electrical system may be limited or will not function. The error memory inside the trailer module may not be able to be accessed by vehicle manufacturers diagnostic system.

Error logs relating to the trailer electrical equipment, that may be generated in the vehicle manufacturers diagnostic system as a result of a test procedure, may be due to the incorrect installation of the towing electric kit or the false activation of the trailer module.

We always recommend whenever possible, the following troubleshooting process:

- An analysis of the vehicle's error memory and possibly clearing of all faults before the start of the installation!
- Try disconnecting the trailer module from the towing harness and re-start the fault clearing process!
   If in doubt, limit the time for troubleshooting to a max of 0,5 hours and call our Technical Support Team!

Please follow our instructions carefully and always test the towing electrics using a true lighting board or a specifically designed bulb tester. If an LED tester is used, ensure it is equipped with correct load resistors or malfunctions will occur!

This instruction is subject to changes and we reserve the right to make changes to design, colour etc.


All of the data and illustrations may not be an exact representation but the text contained in this instruction must be observed!

1/20

ECS Electronics UK The Old Dyehouse Macclesfield Cheshire, SK11 7RN UK

SALE: +44 (0) 7980 847124 TECHNICAL: +44 (0) 7440 202052 WEB: www.ecs-electronicsuk.co.uk

Email-sales: n.lea@ecs-electronics.com Email-technical: t.skinner@ecs-electronics.com





#### **SYMBOL EXPLANATION**

Left (58-L) respectively Right (58-R) tail light  Stop light (54) / high mounted, third stop light (54)  Turn signal indicator left  Turn signal indicator right  Rear fog light(s)  Reversing light(s)  Permanent power supply / 13pin socket, chamber 9  Charging wire for trailer battery / 13pin socket, chamber 10  Trailer / trailer recognition  B+/30  Permanent current power supply  Ground or Earth (31)  Ground connection battery terminal lug  Positive connection battery terminal lug						
high mounted, third stop light (54)  Turn signal indicator left  Turn signal indicator right  Rear fog light(s)  Reverse 0 Reversing light(s)  Permanent power supply / 13pin socket, chamber 9  Charging wire for trailer battery / 13pin socket, chamber 10  Trailer / trailer recognition  B+/30  Permanent current power supply  Ground or Earth (31)  Ground connection battery terminal lug	-\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\					
Turn signal indicator right  Rear fog light(s)  Reverse 0 - Reversing light(s)  Permanent power supply / 13pin socket, chamber 9  Charging wire for trailer battery / 13pin socket, chamber 10  Trailer / trailer recognition  B+/30  Permanent current power supply  Ground or Earth (31)  Ground connection battery terminal lug	54 (STOP)					
Reverse 0 - Reversing light(s)  Reversing light(s)  Permanent power supply / 13pin socket, chamber 9  Charging wire for trailer battery / 13pin socket, chamber 10  Trailer / trailer recognition  B+/30  Permanent current power supply  Ground or Earth (31)  Ground connection battery terminal lug	<u></u> ⟨ <b>∟</b> ∟	Turn signal indicator left				
Reversing light(s)  Permanent power supply / 13pin socket, chamber 9  Charging wire for trailer battery / 13pin socket, chamber 10  Trailer / trailer recognition  B+/30  Permanent current power supply  Ground or Earth (31)  Ground connection battery terminal lug	R⊏	Turn signal indicator right				
Reversing light(s)  Permanent power supply / 13pin socket, chamber 9  Charging wire for trailer battery / 13pin socket, chamber 10  Trailer / trailer recognition  B+/30  Permanent current power supply  Ground or Earth (31)  Ground connection battery terminal lug	105 O\\pm\	Rear fog light(s)				
13pin socket, chamber 9  13pin socket, chamber 9  Charging wire for trailer battery / 13pin socket, chamber 10  Trailer / trailer recognition  B+/30  Permanent current power supply  Ground or Earth (31)  Ground connection battery terminal lug	Reverse 0=	Reversing light(s)				
Trailer / trailer recognition  B+/30  Permanent current power supply  Ground or Earth (31)  Ground connection battery terminal lug	30+ •					
B+/30 Permanent current power supply  Ground or Earth (31)  Ground connection battery terminal lug	15+ •					
Ground or Earth (31)  Ground connection battery terminal lug		Trailer / trailer recognition				
Ground connection battery terminal lug	B+/30	Permanent current power supply				
	<u> </u>	Ground or Earth (31)				
Positive connection battery terminal lug	$\overline{\bigcirc}$	Ground connection battery terminal lug				
	+	Positive connection battery terminal lug				

(12V)	Cigarette lighter / accessory socket					
	Loudspeaker / buzzer					
	Park Distance Control					
-/	Switch / source of function					
<b>→</b>	Connect together					
<b>+</b>	Disconnect					
4	Look at / See further information					
	Look carefully at selected area					
	Present / Occupied / OK					
X CTPL	Not present / Not occupied / Not O					
D ((((	Acoustic indication					
$\triangle$	Attention / important advice					
20 Amp.	Fuse / fuse capacity 20 Ampère					


#### **TOOLS**





#### **ATTENTION!**

The vehicle's cooling capacity may have to be increased when retrofitting a trailer coupling! You must observe the manufacturer's instructions!!



Note: It may be necessary to check if this vehicle has a stored radio code before disconnecting the battery!




## **ATTENTION!**


In order to avoid mal-functions and damage to the vehicle's electrical system the earth terminal **must be disconnected** from the vehicle's battery **before starting work!** 


Both the trailer module and the vehicle's control unit for the electrical system can be damaged during work on the data bus connections if the battery is not disconnected!

1

Please pay attention to the manufacturer's instructions when disconnecting and reconnecting the vehicle's battery!









ECS Electronics UK The Old Dyehouse Macclesfield Cheshire, SK11 7RN UK

SALE: +44 (0) 7980 847124 TECHNICAL: +44 (0) 7440 202052 WEB: www.ecs-electronicsuk.co.uk Email-sales: n.lea@ecs-electronics.com Email-technical: t.skinner@ecs-electronics.com






# SOCKET CONNECTION

DIN/ISO	Ų.	0#	<u></u> 1-7	R☐	<u></u>	STOP	-\\\\\\\
1724	1/L	2	3/31	4/R	5/58-R	6/54	7/58-L
Pmax	21W	42W		21W	52W	3x21W	52W
Colour	Yellow	Blue	White	Green	Brown	Red	Black


9




7/20

ECS Electronics UK The Old Dyehouse Macclesfield Cheshire, SK11 7RN UK


SALE: +44 (0) 7980 847124 TECHNICAL: +44 (0) 7440 202052 WEB: www.ecs-electronicsuk.co.uk Email-sales: n.lea@ecs-electronics.com Email-technical: t.skinner@ecs-electronics.com







0

14









ECS Electronics UK The Old Dyehouse Macclesfield Cheshire, SK11 7RN UK

SALE: +44 (0) 7980 847124 TECHNICAL: +44 (0) 7440 202052 WEB: www.ecs-electronicsuk.co.uk Email-sales: n.lea@ecs-electronics.com Email-technical: t.skinner@ecs-electronics.com



ECS Electronics UK The Old Dyehouse Macclesfield Cheshire, SK11 7RN UK

SALE: +44 (0) 7980 847124 TECHNICAL: +44 (0) 7440 202052 WEB: www.ecs-electronicsuk.co.uk Email-sales: n.lea@ecs-electronics.com Email-technical: t.skinner@ecs-electronics.com




ECS Electronics UK The Old Dyehouse Macclesfield Cheshire, SK11 7RN UK

SALE: +44 (0) 7980 847124 TECHNICAL: +44 (0) 7440 202052 WEB: www.ecs-electronicsuk.co.uk Email-sales: n.lea@ecs-electronics.com Email-technical: t.skinner@ecs-electronics.com

### **OPTIONAL PDC cut-off**

Option 2

Vehicles with after market fitted PDC-System



INFO





Locate the **PDC** (Parking Sensor) Module in the Vehicle. **OPTION 1** When the PDC-system has no specific **MUTE** wire: Locate and cut the wire at **ONE** of the locations A-G and connect to the **ECS Towbar Wiring Kit** as shown in Option 1. Always check if cutting the wire at the selected location does not create any errors in the PDC-system or the vehicle, if so, then select another location. In this case the cut wire is connected and the system operates normally. When the trailer is connected. This wire becomes disconnected by the Trailer Module. If the same module

also controls the Front Sensors then use only locations F or G to prevent the front sensors switching off. **OPTION 2** When the PDC-system has a specific **MUTE** wire: Check in the manual of the PDC-system which input the PDC module requires to switch off the system (+12v or Earth trigger). Then connect the Trigger wire of the PDC system to pin 16 of the ECS connector, and connect the required feed (+12v or Earth) to pin 14 and 18.

**Be careful** as connecting the wrong feed can cause damage to the PDC-system.

Always check Before and After installation the PDC System is working correctly, and where possible any error codes











15/20


ECS Electronics UK The Old Dyehouse Macclesfield Cheshire, SK11 7RN UK


SALE: +44 (0) 7980 847124 TECHNICAL: +44 (0) 7440 202052 WEB: www.ecs-electronicsuk.co.uk


Email-sales: n.lea@ecs-electronics.com Email-technical: t.skinner@ecs-electronics.com

















ELECTRONICS

ELECTRONICS

ELECTRONICS

ELECTRONICS

ELECTRONICS

20/20

ECS Electronics UK The Old Dyehouse Macclesfield Cheshire, SK11 7RN UK

SALE: +44 (0) 7980 847124 TECHNICAL: +44 (0) 7440 202052 WEB: www.ecs-electronicsuk.co.uk Email-sales: n.lea@ecs-electronics.com Email-technical: t.skinner@ecs-electronics.com